Z-PRO









Economical High Performance Taps

For Metric Threads



*Z-PRO PO have a Bright Surface Finish
*AVAILABLE IN TIN AND TICN UPON REQUEST
Custom Blend High Vanadium HSS

The Z-PRO Series is designed for carbon steels, alloyed steels, irons, brass and free machining materials, including stainless steel that requires the most economical tool life, They are ideal for materials that produce stringy chips, such as steels, stainless steels and plastics.

Spiral Pointed taps are recommended for tapping through holes.

Plug Style (3 to 5 threads chamfered)
DIN lengths with ANSI shank dimensions.

Machine Screw Sizes
Z-PRO Series PO
Fractional Sizes

Dividiguis with rivor shall a unicersions.											
TPI	No. of Flutes	Pitch Diameter Limit/ EDP Numbers							Dimensions		
Nominal Size		D5	D6	D7	D8	D9	D10	D11	Length of Thread	Neck Length	Length Overall
M39 X 4	4	_	_	_	_	PS039U9NEB	_	_	2.047	3.858	7.874
M42 X 1*	4	PS042M5NEB	_	_					1.142	3.858	7.874
M42 X 1.5*	4	_	PS042O6NEB	_	_	_	_	_	1.142	3.858	7.874
M42 X 2	4	—	_	PS042Q7NEB	_	_	_	_	1.142	3.858	7.874
M42 X 4.5	4	_	_	_	_	_	PS042VONEE	-	2.323	3.858	7.874
M45 X 1*	4	PS045M5NEB	_	_	_	_	_	_	1.22	4.252	8.661
M45 X 1.5*	4	_	PS045O6NEB	_	_	_	_	_	1.22	4.252	8.661
M45 X 2*	4	_	_	PS045Q7NEB	_	_	_	_	1.22	4.252	8.661
M45 X 3	4	_	_	_	PS045S8NEB	_	_	<u> </u>	2.323	4.252	8.661
M45 X 4.5	4	_	_	_	_	_	PS045VONEB	. —	2.323	4.252	8.661
M48 X 1*	4	_	PS048M6NEB	_	_	_	_	_	1.22	4.803	9.843
M48 X 1.5*	4	_	_	PS048O7NEB	_	_	_	_	1.22	4.803	9.843
M48 X 2*	4	_	_	PS048Q7NEB	_	_	_	<u>—</u>	1.22	4.803	9.843
M48 X 3	4	_	_	_	<u>—</u>	PS048S9NEB	<u>—</u>	<u> </u>	2.559	4.803	9.843
M48 X 5	4	_	_	_	_	_	<u> </u>	PS048W-NEB	2.559	4.803	9.843

^{*}Semi Standard